

DG-LSV2

STANDARD FEATURES

- 4-Wheel Hydraulic braking with Front Disc Brakes
- Double A-arm independent front suspension with adjustable shock absorbers;
- Adjustable camber can keep the tire use longer;
- Double- ended Rack& Pinion steering;
- Higher ground clearance with 120mm;
- Optional 8*6V Battery for longer traveling distance;
- On-board Charging system;
- Downhill, Regenerative braking with Roll-away protection (with key on);
- Digital Display Meter;
- Automotive Glass Windshield;
- Windshield Wiper;



SPECIFICATIONS				OPTIONAL ACCESSORIES	
Battery	8V*6	Overall dimensions	2520*1350*1910mm	Weather enclosure	
Motor	48V4KW	Carrying capacity	250kgs	CD player	
Controller	Curtis	Gross weight	540kgs	USB port	
Range (km)	60	Front wheel Tread (mm)	930	Rear seat kit	
Max. speed (km/h)	40	Rear wheel Tread (mm)	980	Trojan battery	
Minimum turning radius (m)	3.1	Tires	205/50 R 10	High mount stop lamp	
Max. climbing ability	30%	Quantity per Container	8pcs/20GP 17pcs/40HQ		

DG-LSV4

STANDARD FEATURES

- 4-Wheel Hydraulic braking with Front Disc Brakes;
- Double A-arm independent front suspension with adjustable shock absorbers;
- Adjustable camber can keep the tire use longer;
- Double- ended Rack& Pinion steering;
- Higher ground clearance with 120mm;
- Optional 8*6V Battery for longer traveling distance;
- On-board Charging system;
- Downhill, Regenerative braking with Roll-away protection (with key on);
- Digital Display Meter;
- Automotive Glass Windshield;
- Windshield Wiper;



SPECIFICATIONS				OPTIONAL ACCESSORIES	
Battery	8V*6	Overall dimensions	3140*1350*1935mm	Weather enclosure	
Motor	48V4KW	Carrying capacity	480kgs	CD player	
Controller	Curtis	Gross weight	610kgs	USB port	
Range (km)	60	Front wheel Tread (mm)	930	Rear seat kit	
Max. speed (km/h)	40	Rear wheel Tread (mm)	980	Trojan battery	
Minimum turning radius (m)	4.5	Tires	205/50 R-10	High mount stop lamp	
Max. climbing ability	20%	Quantity per Container	2pcs/20GP 6pcs/40HQ		